NYE County NWRPO - Technical Data Report

RID No	D. Transm	nitter	Org.	Receiver	Org.	Key word1	Title/Description				
4810	Downing		NYE	Qarc	NYE	3S	Ewdp-3s Westbay Data, 8/15/01 - 12/27/01				
1	12/27/2001	General Doc. Type	QA PROGRAM	DOC	Keyword2	VB					
Entry Date	1/29/2002	Detailed Doc. Type) DATA		Keyword3	DATA					
Preparer	Reina Downir	ng									
Title of Data	EWDP-3S Westbay Data, 8/15/01 - 12/27/01										
Description of Data	One CD containing an Excel file "122701_3SQA.xls". This file contains water elevation and temperature data from 8/15/01 to 12/27/01 collected at Phase I EWDP-3S Westbay instrumented well.										
Data Collection Method	Westbay Mosdax Datalogger and pressure and temperature probes										
Data Location(s)											
Data Collection Period(s)	8/15/01 to 12/27/01										
Data Source(s)	At EWDP-3S, Westbay datalogger SN 1500 (Probe 0 - atmospheric), Probe 1 (removed from the new well design - RID 4099), Probe 2 (SN 2519) at a depth of 398.2 ft., and Probe 3 (SN 2454) at a depth of 488.3 ft.										
Data Censuring											
Data Processing	Refer to NWRPO Technical Procedure TP-9.2.										
Data Limitations	EWDP-3S Westbay data limitations (data collection period 8/15/01 to 12/27/01). The following text contains additional information necessary for interpretation of the attached EWDP water elevation and temperature data. Listed are the activities and particular environments associated with the well and instrumentation. Time frames are listed for each activity. Certain activities, such as equipment testing or water sampling, may have an impact on the data.										
	EWDP-3S: There are two downhole Westbay monitoring probes at this well location since 3/26/01. Probe 2 is located at 398.2 ft. below ground surface and probe 3 is located 488.3 ft. below ground surface. Each probe is located in a separate packed off zone.										
	11/19/01 Duplicate data exists in RID 4863 due to time change for Daylight Savings Time.										
	12/6/01 - Remove probe string from the well for factory calibration. Install MDL 2291, Probe 2 (SN 2446), and Probe 3 (SN 2202). Probe 2 did not engage in port; no subsequent data recorded.										
Governing QA Docs.	TP-9.2										
Frequency of Transmittal	Once per quarter										
Direct Questions	-										

NYE County NWRPO - Technical Data Report

F	RID No.	Transmitter	Org.	Receiver	Org.	Key word1	Title/Description
DIIGOLAU							
About	Data						
То	-						

_